

4 POLI -poles-polig-1500 min/-1 v 230/400 - Hz 50

COD IMB3 - GRA	POTENZA NOMINA	VELOCITA' NOMI	INTENSITA' NOM	FATTORE DI POT	RENDIMENTOEFFE	CORRENTE D'AVV	COPPIA NOMINAL	COPPIA D'AVVIA	COPPIA MASSIMA	MOMENTO D'INER	PESOIMB3WEIGTI
A1003B1100 GR-56	0.06	1370	0.25 ĩ»	0.7	47.8	2.7	0.41	2	2.2	0.0022	3
A2003B1100 GR-56	0.09	1370	0.34 ĩ»	0.68	55.9	2.9	0.635	2	2.2	0.0025	3.1
A3003B1100 GR-56	0.12	1370	0.53 ĩ»	0.59	56.1	3	0.86	2.2	2.2	0.0035	3.2
B0003B1100 GR-63	0.12	1340	0.48 ĩ»	0.75	47.6	3.6	0.85	2.3	2.3	0.0042	3.8
B1003 B1100 GR-63	0.18	1345	0.77 ĩ»	0.6	57.2	3.7	1.31	2.3	2.2	0.0047	4.1
B2003B1100 GR-63	0.25	1360	0.85 ĩ»	0.66	63.8	4.2	1.75	2.2	2.6	0.0056	4.8
C1003B1100 GR-71	0.25	1425	0.82 ĩ»	0.64	67.6	4.6	1.68	2.4	2.7	0.0067	5.7
C2003B1100 GR-71	0.37	1418	1.11 ĩ»	0.68	70.1	4.4	2.49	2.3	2.6	0.0085	6.4
C3003B1100 GR-71	0.55	1400	1.59 ĩ»	0.69	72	3.7	3.76	1.9	2.2	0.0111	7.7
D1003B1100 GR-80	0.55	1400	1.65 ĩ»	0.76	63.2	4.4	3.78	2.1	2.2	0.0132	8.3
C5003B1100 GR-71	0.75	1400	1.98 ĩ»	0.72	75.8	3.8	5.15	2	2.1	0.0113	8.5
D3003B1100 GR-80	0.75	1410	1.9 ĩ»	0.78	72.8	4.5	5.1	2.4	2.3	0.0181	9.2
D5003B1100 GR-80	0.95	1425	2.3 ĩ»	0.75	79.7	5.7	6.35	2.6	2.8	0.0241	11
D6003B1100 GR-80	1.1	1410	2.9 ĩ»	0.78	71.8	5.4	7.69	2.3	2.7	0.0263	11.3
D7003B1100 GR-80 *	1.5	1408	2.72 ĩ»	0.78	77.8	5.2	7.69	2.2	2.5	0.0032	11.4
G1003B1100 GR-90S	1.1	1430	3.8 ĩ»	0.74	78.4	5.1	10.26	2.5	2.5	0.00295	12.8
I1003B1100 GR-90L	1.5	1420	3.75 ĩ»	0.74	78.3	5.2	10.14	2.8	3	0.00391	13.5
I3003B1100 GR-90L	1.84	1400	4.5 ĩ»	0.78	79.1	5.8	12.46	2.6	2.4	0.00493	15.6
I4003B1100 GR-90L	2.2	1430	5.3 ĩ»	0.69	86.4	5.7	14.78	2	2.1	0.00523	16.9
M1003B1100 GR-100	2.2	1430	5.2 ĩ»	0.76	81.9	5.3	15.27	1.9	2.3	0.00473	18
M2003B1100 GR-100	3	1435	6.8 ĩ»	0.74	83.6	5.2	19.79	2.4	2.3	0.00536	21.5
M3003B1100 GR-100 **	4	1435	8.9 ĩ»	0.78	83.7	5.5	27.3	2.4	2.5	0.00647	24.5
O1003B1100 GR-112	4	1450	8.8 ĩ»	0.76	85.7	5.6	26.75	2.5	2.6	0.00711	28.5
O2003B1100 GR-112 **	5.5	1430	12 ĩ»	0.8	86.6	6.1	36.76	2.5	2.4	0.00952	33.5
Q1003B1100 GR-132	5.5	1460	12 ĩ»	0.75	87.5	6.3	36.15	2.4	2.5	0.01775	42.5
R1003B1100 GR-132	7.5	1455	17 ĩ»	0.76	83.4	7.6	49.83	2.7	3	0.03324	51
R2003B1100 GR-132 **	9.2	1455	17.2 ĩ»	0.84	91.9	7.8	60.58	3	3.2	0.03819	62
R3003B1100 GR-132 **	11	1455	25 ĩ»	0.77	80.6	7.7	72.3	3.1	3.1	0.04812	65
T1003B1100 GR-160	11	1465	26 ĩ»	0.71	86.5	5.8	71.93	2.2	2.5	0.05145	91
U1003B1100 GR-160	15	1460	31 ĩ»	0.79	88.6	6.5	99.05	2.7	2.8	0.07342	94
U2003B1100 GR-160	18.4	1460	39 ĩ»	0.76	90.3	6.7	120.7	2.8	2.9	0.08134	117
U3003B1100 GR-160 **	22	1470	49 ĩ»	0.72	89.3	6.1	142.8	2.6	2.7	0.0894	117

